Appassionato



 Distortion THD +N:
 ≤ 0,03 %

 Channel- selection:
 ≥ 92 dB

 Channel- balance L/R:
 ≤ 0,15 dB

 Dynamic range:
 ≥ 96 dB

 Output- resistance:
 ≤ 200 Ω

 Laser- unit:
 Philips

 D/A converter:
 Crystal, 24 Bit

Specials: Class A output single ended triode tube stage, with 6 LUA- tubes

4 x 12AX7 / 2 x 12 AT 7, 7 power-supplies a.s.o..

New in market! From D/A converter to output totally designed with tubes (no semiconductors used) including sampling filter. Only finest WIMA MKP 10 double- layer, polypropylene coup ling capacitors, selected to 0,2 % tolerenace are used in signal path. 2 similar RCA- cinch- outputs, providing a convenient

connection for a separate headphone- amplifier.

Power consumption standby: $\leq 0.1 \text{ W}$

Dimensions: $W \times H \times D$: 44 x 11,6 x 37 cm Gross/ net weight: 19,2 kgs / 15,2 kgs


Design: mirror polished stainless steel front panel dark blue cabinet,

including metal IR remote control.


All data typical. All alterations are reserved without any notice and information of customer in view of improvement of specified data in this brochure.



LUA APPASSIONATO All mesaurements made with selected LUA- tubes or equivalent Svetlana, Sovtek, Golden Dragon, a.o..




Frequency-response 10Hz - 20kHz, $\leq \pm 0.15dB$ Channel-Balance $\leq \pm 0.1dB$, Interchannel phase $\leq \pm 0.2^{\circ}$




THD+ N 0 dB Signal, K_2 - 70, K_3 -95dB

Luas Appassionato is a big step ahead in the world market of recommanded CD-players with its new designed 6- tubes single ended Class A output- stage. One of its specialities is, that there are not used any semiconductors. Directly from D/A- converter output, the output amplifier, as same as the analogue part of the sampling filter is designed completly in tube technology. True to its tradition of outstanding quality, Lua creats different remarkable CD players as for example the Cantilena SEL. This well noticed model enjoyed the best test results in the market with many hundreds being sold. But Lua wanted more. The experience with the first CD-player gave our engineers the chance to create a much better version named Appassionato. This Appassionato was to embody the best possible sound reproduction and so a well-known Crystal Clear was integrated. For the transport mechanism, Lua selected a



Time domain display of signal



Left and right noise spectrum Infinity zero- 132 dB / 1kHz, perfect for a tube stage.

Philips- version, which delivers the best technical results at a modest price. A big breakthrough was the newly designed 6-tube single ended triode Class A output section with an output impedance of only 180 Ohms. And speaking of outputs, a speciality of all LUA CD- players is the provision of two outputs instead of one. The second output can drive a separate headphone- amplifier without use of the main amplifier. This is also interesting for dealers, enabling connection to two different amplifiers allowing their sound quality to easily be compared using a single CD player as source. Also sonic comparisons between two different brands of RCA interlinks (Cinch cables) can in the same way be easily made by connecting them to two different high level inputs of your amplifier, especially if it is equipped with a remote controlled channel switching facility.